

<b>Declaration of Performance</b> according to Annex III of the regulation (EU) No 305/2011 for the product <b>vapour barrier 200 µm</b>		
0	Reference Number	202022/19/06/05
1	Code	Vapour barrier 200 - 202022
2	Batch Number	See label on product
3	Designated use	Sealing vapour barrier made of polyethylene, for controlled sealing of constructions
4	Trade name / manufacturer	Vapour barrier / vliepa GmbH, Heidhausen 81, 41379 Brüggen
5	Authorized agent	Not applicable
6	System of assessment	System 3
7	Declaration of performance by hEU Norm	The notified body, code 1213 has carried out the product type approval test under system 3 and has issued the following: Test report no 72185/06-X
8	-	-

9	Declared performance	Essential characteristics	Performance	Harmonized technical specification
		Reaction to fire	Class E	
Resistance to water penetration 2 kPa	passed			
Water vapour permeability	>250 m			
Tensile strength: MD / CD	350 / 350 N/5cm			
Elongation: MD / CD	500 / 500 %			
Resistance to impact load	300 mm			
Tear resistance: MD / CD	300 / 300 N			
Heat of combustion	7.900 kJ/m <sup>2</sup>			
Durability	passed			
Hazardous substances	none			
Thickness	200 µm			
Length	25 m			
Width	4 m			

Declaration: The performance of the product identified in point 1 and 2 is in conformity with the declared performance in point 9.  
 This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.  
 Signed for and on behalf of the manufacturer by the plant manager.

ppa. Gerald Richter, Production Manager  
 Brüggen, 05.06.2019

