

	accordi	Declaration of Performance ing to Annex III of the regulation (EU) No 305/2011						
	for the product							
vapour barrier 400 µm								
0	Reference Number	202009/19/06/05						
1	Code	Vapour barrier 400 - 202009						
2	Batch Number	See label on product						
3	Designated use	Sealing vapour barrier made of polyethylene, for controlled sealing of constructions						
4	Trade name / manufacturer	Vapour barrier / vliepa GmbH, Heidhausen 81, 41379 Brüggen						
5	Authorized agent	Not applicable						
6	System of assessment	System 3						
7	Declaration of performance by hEU Norm	The notified body, code 1213 has carried out the product type approval test under system 3 and has issued the following: Test report no 72185/06-X						
8	-	-						

		Essential characteristics	Performance	Harmonized technical specification		
	Declared performance	Reaction to fire	Class E	EN 13984:2013		
		Resistance to water penetration 2 kPa	passed			
		Water vapour permeability	>380 m			
		Tensile strength: MD / CD	390 / 340 N/5cm			
		Elongation: MD / CD	600 / 620 %			
		Resistance to impact load	300 mm			
9		Tear resistance: MD / CD	270 / 260 N			
		Shear resistance of joints	NPD			
		Combustion heat	NPD			
		Durability	passed			
		Hazardous substances	none			
		Thickness	400 µm			
		Length	25 m			
		Width	4 m			

Declaration: The performance of the product identified in point 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4. Signed for and on behalf of the manufacturer by the plant manager.

ppa. Gerald Richter, Production Manager Brüggen, 05.06.2019