

<b>Declaration of Performance</b> according to Annex III (EU) Nr. 305/2011 <b>Vapour barrier 400 µm</b>		
0	Reference Number	200061/14/07/11
1	Code	Vapour barrier 400 - 200061
2	Charge Code	see label on product
3	Purpose	Sealing sheet made of Polyethylen as water vapour barrier, for controlled sealing of constructions
4	Trade Name / Manufacturer	vliepa GmbH, Heidhausen 81, 41379 Brüggen
5	Representative	not applicable
6	System of assessment	System 3
7	Declaration of performance on the basis of hEU Norm	The notifying body, code number 0761, has carried out the type approvals of System 3 and issued the following: Test report
8	Declaration of performance on the basis of EU TB	not applicable

9	Declared performance	Essential characteristics	Performance	Harmonized technical specification
		Reaction to fire	class E	EN 13984:2004+A1:2006
Resistance to water penetration 2 kPa	passed			
Water vapour permeability	200 m			
Tensile strength: MD / CD	300 / 280 N/5cm			
Elongation: MD / CD	250 / 400 %			
Resistance to impact	NPD			
Tear resistance: MD / CD	200 / 200 N			
Shear strength of joining seams	NPD			
Heat of combustion	NPD			
Durability	passed			
Hazardous substances	none			
Thickness	400 µm			
Length	25 m			
Width	4 m			

Declaration: The performance of the product identified in point 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4. Signed for and on behalf of the manufacturer by the plant manager.

ppa. Gerald Richter, Production Manager  
 Brüggen, 21.09.2015

