

<b>Declaration of Performance</b> according to (EU) Nr. 305/2011  <b>Vapour barrier sheet 200 µm</b>		
0	Reference Number	200060/13/06/11
1	Code	Vapour barrier sheet 200 - 200060
2	Charge Number	see label on product
3	Purpose	Airtight and vapour barrier for interior and loft conversions
4	Manufacturer	vliepa GmbH, Heidhausen 81, 41379 Brüggen
5	Appointed Agent	not relevant
6	System of assessment	System 3
7	Declaration of performance by a harmonised standard	Following notified bodies have carried out the type approvals System 3. Testing Institut ID-No.0761, Report No. 5137/2506
8	-	-

	Declared performance	Essential characteristics	Performance	Harmonized technical specification
		9	Reaction to fire	Class E
	Resistance to water penetration 2 kPa	passed		
	Water vapour transmission	>100 m		
	Tensile strength: MD / CD	170 / 150 N/5cm		
	Elongation: MD / CD	250 / 400 %		
	Resistance to impact	NPD		
	Tear resistance: MD / CD	105 / 110 N		
	Durability	passed		
	Hazardous substances	no		
	Thickness	200 µm		
	Length	25 m		
	Width	4 m		

Declaration: The performance of the product identified in point 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4. Signed for and on behalf of the manufacturer by the plant manager.

ppa. Gerald Richter  
Brüggen, 11.06.2013

