

Declaration of Performance according to (EU) Nr. 305/2011 Vapour barrier sheet 200 µm		
0	Reference Number	200039/13/06/11
1	Code	Vapour barrier sheet 200 - 200039
2	Charge Number	see label on product
3	Purpose	Airtight and vapour barrier for interior and loft conversions
4	Manufacturer	vliepa GmbH, Heidhausen 81, 41379 Brüggen
5	Appointed Agent	not relevant
6	System of assessment	System 3
7	Declaration of performance by a harmonised standard	Following notified bodies have carried out the type approvals System 3. Testing Institut ID-No.1213, Report No. 72185/06-x
8	-	-

9	Declared performance	Essential characteristics	Performance	Harmonized technical specification
		Reaction to fire	Class E	EN 13984:2004+A1:2006
Resistance to water penetration 2 kPa	passed			
Water vapour transmission	>140 m			
Tensile strength: MD / CD	175 / 160 N/5cm			
Elongation: MD / CD	500 / 570 %			
Resistance to impact	300 mm			
Tear resistance: MD / CD	130 / 135 N			
Durability	passed			
Hazardous substances	no			
Thickness	200 µm			
Length	25 m			
Width	6 m			

Declaration: The performance of the product identified in point 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4. Signed for and on behalf of the manufacturer by the plant manager.

ppa. Gerald Richter
Brüggen, 11.06.2013

